



# GreenPerform Panel

## RC160V LED40S 865 W60L60 PSU

- - Wide beam - Polystyrene bowl/cover prismatic - 110°

GreenPerform Panel is the slimmest Panel with highest efficacy in the market. It offers two lumen options with four dimension types, 200X1200, 300X1200, 600x600,600x1200, and three mounting options, recessed, suspended and plaster ceiling.

### Product data

General Information	
Beam angle of light source	- °
Lamp colour code	865 cool daylight
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	No [-]
Driver included	Yes
Optic type	WB [ Wide beam]
Optical cover/lens type	Polystyrene bowl/cover prismatic
Luminaire light beam spread	110°
Control interface	-
Connection	CI [ Internal connector]
Cable	-
Protection class IEC	Safety class II (II)
Glow-wire test	650/30 [ Temperature 650 °C, duration 30 s]
Flammability mark	NO [-]
CE mark	CE mark
ENEC mark	-
Warranty period	3 years
Constant light output	No

Number of products on MCB (16 A type B)	90
EU RoHS compliant	Yes
Light source engine type	LED

### Operating and Electrical

Input Voltage	220 to 240 V
Input frequency	50 to 60 Hz
Initial CLO power consumption	NA W
Average CLO power consumption	NA W
Inrush current	15.8 A
Inrush time	181 ms
Power factor (min.)	0.9

### Controls and Dimming

Dimmable	No
----------	----

### Mechanical and Housing

Housing material	Aluminium
Reflector material	-
Optic material	Polystyrene

## GreenPerform Panel

Optical cover/lens material	Polystyrene
Fixation material	Steel
Optical cover/lens finish	Frosted
Overall length	595 mm
Overall width	595 mm
Overall height	8.3 mm
Colour	White

### Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]

### Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	4000 lm
Luminous flux tolerance	+/-5%
Initial LED luminaire efficacy	110 lm/W
Lamp colour temperature	6500 K
Colour Rendering Index	>80
Initial chromaticity	(0.43, 0.40) SDCM<4

Initial input power	36 W
Power consumption tolerance	+/-10%

### Application Conditions


Ambient temperature range	-20 to +45 °C
Maximum dimming level	Not applicable

### Product Data

Full product code	911401719512
Order product name	RC160V LED40S 865 W60L60 PSU
Order code	911401719512
SAP numerator – quantity per pack	1
Numerator – packs per outer box	2
SAP material	911401719512
SAP net weight (piece)	0.799 kg



## Dimensional drawing



SmartPanel 2.0 RC160V

