

UniStrip G4

BCP382 9LED 40K 24V A2 L30 DMX

UniStrip G4 - 659 lm - 9 W - 4000 K

UniStrip G4 is a surface-mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.;One family that fits all your needs, wall washing, grazing and also linear flood lighting.;The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.;Available in white, monochromatic colours, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

| General Information | | Serviceability class | |
|-----------------------------|--|--|---------|
| Lamp colour code | Neutral white | Class B, the luminaire is equipped with some serviceable parts (when applicable): driver, control units, surge-protection device, front cover and mechanical parts | |
| Light source replaceable | No | Operating and Electrical | |
| Driver included | No | Input Voltage | 24 DC V |
| Optical cover/lens type | CLFT [Clear flat] | Input frequency | - Hz |
| Luminaire light beam spread | 16° x 35° | Power factor (min.) | 0.9 |
| Control interface | Dynamix DMX | Controls and Dimming | |
| Connection | 2 push-in connectors 5-pole | Dimmable | Yes |
| Cable | 2 cables 0.15 m with connectors 5-pole | | |
| Protection class IEC | Safety class III (III) | | |
| Flammability mark | F [For mounting on normally flammable surfaces] | | |
| CE mark | CE mark | | |
| Light source engine type | LED | | |

UniStrip G4

Mechanical and Housing

| | |
|-----------------------------|------------------------------------|
| Housing material | Aluminum extruded |
| Optic material | Polymethyl methacrylate |
| Optical cover/lens material | Tempered glass |
| Fixation material | Aluminium |
| Mounting device | MBA [Mounting bracket adjustable] |
| Optical cover/lens finish | Clear |
| Overall length | 300 mm |
| Overall width | 38 mm |
| Overall height | 47 mm |
| Colour | Dark Grey |

Approval and Application

| | |
|------------------------------|---|
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [1 J] |

Initial Performance (IEC Compliant)

| | |
|-------------------------------------|---------|
| Initial luminous flux (system flux) | 659 lm |
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 73 lm/W |
| Lamp colour temperature | 4000 K |

| | |
|-----------------------------|--------|
| Colour Rendering Index | 80 |
| Initial chromaticity | 4 SDCM |
| Initial input power | 9 W |
| Power consumption tolerance | +/-10% |

Application Conditions


| | |
|---------------------------|---------------|
| Ambient temperature range | -40 to +50 °C |
|---------------------------|---------------|

Product Data

| | |
|-----------------------------------|--------------------------------|
| Full product code | 871951494501299 |
| Order product name | BCP382 9LED 40K 24V A2 L30 DMX |
| EAN/UPC – product | 8719514945012 |
| Order code | 911401739692 |
| SAP numerator – quantity per pack | 1 |
| Numerator – packs per outer box | 30 |
| SAP material | 911401739692 |
| SAP net weight (piece) | 0.599 kg |



Dimensional drawing



BCP382 9LED 40K 24V A2 L30 DMX

