



# UniDot G2

## BGS300 G2 12LEDLP RGB 24V CFC DMX

68 lm - 3 W - - K

UniDot G2 is a surface-mounted, exterior-rated and compact-sized architectural LED direct-view dot lighting luminaire that is designed for façade and outdoor lighting applications. The robust mechanical and unique optical covers make UniDot G2 ideal for building facades, bridges, theatres, amusement parks and recreational centres. Available in white, monochromatic colours, RGB, RGBW and tunable white. Three optical cover options and a DMX control interface is available to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

### Product data

General Information	
Lamp colour code	Red, green and blue
Light source replaceable	No
Driver/power unit/transformer	PSU-E [ Power supply unit external (PSU)]
Driver included	No
Optical cover/lens type	Polycarbonate bowl/cover flat
Luminaire light beam spread	110°
Control interface	Dynamix DMX
Connection	2 push-in connectors 5-pole
Cable	2 cables 0.3 m with connector 5-pole
Protection class IEC	Safety class III (III)
Flammability mark	F [ For mounting on normally flammable surfaces]
CE mark	CE mark
Light source engine type	LED
Serviceability class	Class B, the luminaire is equipped with some serviceable parts (when applicable): driver, control

  

	units, surge-protection device, front cover and mechanical parts
--	--

  

Light Technical	
Standard tilt angle post-top	-
Standard tilt angle side entry	-

  

Operating and Electrical	
Input Voltage	24 DC V
Input frequency	- Hz
Power factor (min.)	0.9

  

Controls and Dimming	
Dimmable	Yes

  

Mechanical and Housing	
Housing material	Aluminum die-cast

## UniDot G2

Optical cover/lens material	Polycarbonate
Mounting device	No [ - ]
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	78 mm
Overall width	72 mm
Overall height	35 mm
Overall diameter	72 mm
Colour	Dark Grey

### Approval and Application

Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [ 1 J]

### Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	68 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	23 lm/W
Lamp colour temperature	- K

Colour Rendering Index	-
Initial input power	3 W
Power consumption tolerance	+/-10%

### Application Conditions

Ambient temperature range	-40 to +50 °C
Maximum dimming level	1%

### Product Data

Full product code	911401752382
Order product name	BGS300 G2 12LEDLP RGB 24V CFC DMX
Order code	911401752382
SAP numerator – quantity per pack	1
Numerator – packs per outer box	48
SAP material	911401752382
SAP net weight (piece)	0.212 kg



## Dimensional drawing



BGS301/302 UNI Dot

