



# ZXP399 DMX Controls and Accessories

## ZXP399 sub-controller 12V 16 port DMX

12 DC V - - Hz - Finger-protected - CE mark - Black

The ZXP399 DMX Controls and Wiring Accessories are to be used with our architectural and facade lighting luminaires (UniFlood C, M and G, UniStrip G4, UniEdge, UniDot G2, UniString and UniBar).;DMX Controls include a main controller, stand-alone controller, sub-controllers, DMX amplifier and DMX addressing device.;Main Controller: Industrial computer that can control up to 6,000 DMX universes.;Stand-alone Controller: Fits all medium applications with up to 700 DMX universes.;Wiring accessories include leader and jump cables with male and female IP67 connectors and end-caps.;Addressing Device: Hand-held device that can write DMX addresses to a whole run on-site within minutes.;DMX Amplifier: Compact, IP65 and low-power repeater that can amplify the DMX signal for up 100 metres.

### Product data

General Information		Approval and Application	
CE mark	CE mark	Overall width	193 mm
Colour	Black	Overall height	66 mm
		Dimensions (height x width x depth)	66 x 193 x 482 mm (2.6 x 7.6 x 19 in)
Operating and Electrical		Product Data	
Input Voltage	12 DC V	Full product code	911401756642
Input frequency	- Hz	Order product name	ZXP399 sub-controller 12V 16 port DMX
Mechanical and Housing			
Overall length	482 mm		

## ZXP399 DMX Controls and Accessories

Order code	911401756642
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	911401756642

SAP net weight (piece)	2.899 kg
------------------------	----------



### Dimensional drawing



ZXP399

