

UniStrip G4

BCP386 30LED 40K 24V 45 L50 DMX

520 lm - 7.5 W - 4000 K

UniStrip G4 is a surface-mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.; One family that fits all your needs, wall washing, grazing and also linear flood lighting.; The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.; Available in white, monochromatic colours, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

General Information		Power factor (min.)		0.9
Lamp colour code	Neutral white	Controls and Dimming		
Driver included	No	Dimmable	Yes	
Optical cover/lens type	GC [Clear glass]	Mechanical and Housing		
Control interface	Dynamic DMX	Housing material	Aluminum extruded	
Connection	2 push-in connectors 5-pole	Optical cover/lens material	Polymethyl methacrylate	
Cable	2 cables 0.15 m with connectors 5-pole	Overall length	500 mm	
Protection class IEC	Safety class III (III)	Overall width	25.4 mm	
CE mark	CE mark	Overall height	71.6 mm	
		Colour	Dark Grey	
Operating and Electrical				
Input Voltage	24 DC V			
Input frequency	- Hz			

UniStrip G4

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	520 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	69 lm/W
Lamp colour temperature	4000 K
Colour Rendering Index	80
Initial input power	7.5 W
Power consumption tolerance	+/-10%

Application Conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Product Data

Full product code	871951451385399
Order product name	BCP386 30LED 40K 24V 45 L50 DMX
EAN/UPC – product	8719514513853
Order code	911401780202
SAP numerator – quantity per pack	1
Numerator – packs per outer box	50
SAP material	911401780202
SAP net weight (piece)	0.456 kg



Dimensional drawing



BCP386 30LED 40K 24V 45 L50 DMX

