



Electronic ignitor for HID lamp circuits

SN 56

HID ignitors for semi-parallel systems


Product data

General Information	
Application code	56
Operating and Electrical	
Input Voltage	220 to 240 V
Input frequency	50 to 60 Hz
Ignition type	Semi-Parallel
Ignition voltage (max.)	5.0 kV
Ignition voltage (min.)	2.8 kV
Response voltage	196 V
Mains voltage performance (AC)	-8%+6%
Mains voltage safety (AC)	-10%+10%
Power losses (nom.)	1.5 W
Wiring	
Ballast contact wire cross section	0.50-2.50 mm ²
Connector type	Screw
Temperature	
T-ambient (max.)	55 °C

T-ambient (min.)	-20 °C
T-Case maximum (max.)	60 °C
Mechanical and Housing	
Housing	Akulon S223
Approval and Application	
Approval marks	CE marking
Product Data	
Full product code	697013372885700
Order product name	SN 56
EAN/UPC – product	6970133728857
Order code	913710010713
SAP numerator – quantity per pack	1
Numerator – packs per outer box	20
SAP material	913710010713
SAP net weight (piece)	0.079 kg

Electronic ignitor for HID lamp circuits

Dimensional drawing



Product	C1	A1	A2	B1
SN 56	38.5 mm	114.5 mm	95.0 mm	41.5 mm

SN 56

