



Essential LEDtube - Affordable LED solution

Essential LEDtube

Essential LEDtube is an affordable LED tube that is suitable for replacing T8 fluorescent lamps. The product provides a natural lighting effect for use in general lighting applications, as well as instant energy savings – an environmentally friendly solution.

Benefits

- Reduced electricity costs thanks to significant energy savings
- Longer lifetime minimizes re-lamping for reduced maintenance costs
- A better choice for the environment – no mercury

Features

- Affordable LED replacement for T8 fluorescent lamps
- Energy consumption less than half that of normal fluorescent lamps
- 25,000 hours lifetime, double that of normal fluorescent lamps
- No mercury; glass-free tube – no breakage concerns

Application


- Retail, offices
- Industry, warehouses, public places, schools, hospitals, car parks

Essential LEDtube

Versions



Dimensional drawing



A3

Product	D1	D2	A1	A2	A3
CorePro LEDtube 1200mm 16W865 G5 I APR	15.8 mm	19 mm	1149 mm	1156.1 mm	1163.2 mm
CorePro LEDtube 1200mm 16W830 G5 I APR	15.8 mm	19 mm	1149 mm	1156.1 mm	1163.2 mm
CorePro LEDtube 1200mm 16W840 G5 I APR	15.8 mm	19 mm	1149 mm	1156.1 mm	1163.2 mm
CorePro LEDtube 600mm 8W840 G5 I APR	15.8 mm	19 mm	549 mm	556.1 mm	563.2 mm

Product	D1	D2	A1	A2	A3	C	D
LEDtube 600mm	25.68	28	588.5	595.5	602.5	602.5	27.8
8W 765 T8 AP I G	mm	mm	mm	mm	mm	mm	mm
CorePro LEDtube HO 1200mm	25.7 mm	28	1198	1205	1212 mm		
18W865T8 AP							

Essential LEDtube

Controls and Dimming

Dimmable	No
----------	----

Operating and Electrical

Input Frequency	50 to 60 Hz
Starting Time (Nom)	0.5 s

Light Technical

Llmf At End Of Nominal Lifetime (Nom)	70 %
---------------------------------------	------

Mechanical and Housing

Bulb Shape	Tube, double-ended
------------	--------------------

Temperature

T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h	Energy Efficiency Label (EEL)
929001184838	LEDtube 600mm 8W 765 T8 AP I G	8 kWh	A+
929001380708	CorePro LEDtube 600mm 8W840 G5 I APR	8 kWh	A++
929001380908	CorePro LEDtube 1200mm 16W830 G5 I APR	16 kWh	A++
929001381008	CorePro LEDtube 1200mm 16W840 G5 I APR	16 kWh	A++
929001381108	CorePro LEDtube 1200mm 16W865 G5 I APR	16 kWh	A++
929001383508	CorePro LEDtube HO 1200mm 18W865T8 AP	18 kWh	A+

Operating and Electrical

Order Code	Full Product Name	Voltage (Nom)	Power (Rated) (Nom)
929001184838	LEDtube 600mm 8W 765 T8 AP I G	220-240 V	8 W
929001380708	CorePro LEDtube 600mm 8W840 G5 I APR	100-240 V	8 W
929001380908	CorePro LEDtube 1200mm 16W830 G5 I APR	100-240 V	16 W
929001381008	CorePro LEDtube 1200mm 16W840 G5 I APR	100-240 V	16 W

Order Code	Full Product Name	Voltage (Nom)	Power (Rated) (Nom)
929001381108	CorePro LEDtube 1200mm 16W865 G5 I APR	100-240 V	16 W
929001383508	CorePro LEDtube HO 1200mm 18W865T8 AP	220-240 V	18 W

General Information

Order Code	Full Product Name	Cap-Base	Nominal Lifetime (Nom)	Switching Cycle
929001184838	LEDtube 600mm 8W 765 T8 AP I G	G13	15000 h	50,000X
929001380708	CorePro LEDtube 600mm 8W840 G5 I APR	G5	30000 h	50,000X
929001380908	CorePro LEDtube 1200mm 16W830 G5 I APR	G5	30000 h	50,000X

Order Code	Full Product Name	Cap-Base	Nominal Lifetime (Nom)	Switching Cycle
929001381008	CorePro LEDtube 1200mm 16W840 G5 I APR	G5	30000 h	50,000X
929001381108	CorePro LEDtube 1200mm 16W865 G5 I APR	G5	30000 h	50,000X
929001383508	CorePro LEDtube HO 1200mm 18W865T8 AP	G13	30000 h	200,000X

Light Technical (1/2)

Essential LEDtube

Order Code	Full Product Name	Beam		Correlated	Colour
		Angle (Nom)	Colour Code	Colour Temperature (Nom)	Rendering Index (Nom)
929001184838	LEDtube 600mm 8W 765 T8 AP I G	240 °	765	6500 K	73
929001380708	CorePro LEDtube 600mm 8W840 G5 I APR	200 °	840	4000 K	80
929001380908	CorePro LEDtube 1200mm 16W830 G5 I APR	200 °	830	3000 K	80
929001381008	CorePro LEDtube 1200mm 16W840 G5 I APR	200 °	840	4000 K	80

Order Code	Full Product Name	Beam		Correlated	Colour
		Angle (Nom)	Colour Code	Colour Temperature (Nom)	Rendering Index (Nom)
929001381108	CorePro LEDtube 1200mm 16W865 G5 I APR	200 °	865	6500 K	80
929001383508	CorePro LEDtube HO 1200mm 18W865T8 AP	240 °	865	6500 K	80



Light Technical (2/2)

Order Code	Full Product Name	Luminous Flux (Nom)
929001184838	LEDtube 600mm 8W 765 T8 AP I G	800 lm
929001380708	CorePro LEDtube 600mm 8W840 G5 I APR	1050 lm
929001380908	CorePro LEDtube 1200mm 16W830 G5 I APR	2000 lm

Order Code	Full Product Name	Luminous Flux (Nom)
929001381008	CorePro LEDtube 1200mm 16W840 G5 I APR	2100 lm
929001381108	CorePro LEDtube 1200mm 16W865 G5 I APR	2100 lm
929001383508	CorePro LEDtube HO 1200mm 18W865T8 AP	2100 lm

Temperature

Order Code	Full Product Name	T-Case Maximum (Nom)
929001184838	LEDtube 600mm 8W 765 T8 AP I G	60 °C
929001380708	CorePro LEDtube 600mm 8W840 G5 I APR	70 °C
929001380908	CorePro LEDtube 1200mm 16W830 G5 I APR	70 °C
929001381008	CorePro LEDtube 1200mm 16W840 G5 I APR	70 °C
929001381108	CorePro LEDtube 1200mm 16W865 G5 I APR	70 °C
929001383508	CorePro LEDtube HO 1200mm 18W865T8 AP	65 °C



Essential LEDtube

