



# Truefashion Projector GCGM

## ST700T LED40 930PC PSU MB 1C BK

Power supply unit - Beam angle 24° - Lens - 24°

The Truefashion Projector is targeted towards the mid-high-end retail segment with an attractive outlook design, excellent quality of light and dedicated light recipes, as well as system connectivity, in order to create a comfortable ambience and impressive shopping experience to stimulate sales for retail customers.

### Warnings and Safety

- 3 years

### Product data

General Information		Operating and Electrical	
Beam angle of light source	120°	ENEC mark	-
Lamp colour code	930 warm white	Warranty period	3 years
Light source replaceable	No	Constant light output	No
Number of gear units	1 unit	Number of products on MCB (16 A type B)	-
Driver/power unit/transformer	PSU [ Power supply unit]	EU RoHS compliant	Yes
Driver included	Yes	LED engine type	-
Optic type	24 [ Beam angle 24°]	Controls and Dimming	
Optical cover/lens type	Lens	Dimmable	No
Luminaire light beam spread	24°		
Control interface	-		
Connection	Track		
Cable	-		
Protection class IEC	Safety class II (II)		
CE mark	CE mark		

# Truefashion Projector GCGM

## Mechanical and Housing

Housing material	Aluminium
Reflector material	-
Optic material	Polymethyl methacrylate
Optical cover/lens material	Polymethyl methacrylate
Fixation material	Aluminium
Optical cover/lens finish	Clear
Overall length	223 mm
Overall height	185 mm
Overall diameter	80 mm
Colour	Black

## Approval and Application

Ingress protection code	IP20 [ Finger-protected]
Mech. impact protection code	-

## Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	3299.16 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	75.3 lm/W
Lamp colour temperature	3000 K
Colour Rendering Index	>90
Initial chromaticity	(0.422, 0.386) SDCM<3
Initial input power	43.8 W

Power consumption tolerance	+/-10%
-----------------------------	--------

## Over Time Performance (IEC Compliant)

Median useful life L70B50	50000 h
Median useful life L80B50	38700 h
Median useful life L90B50	18200 h

## Application Conditions


Ambient temperature range	-20 to +35 °C
Maximum dimming level	Not applicable
Suitable for random switching	No

## Product Data

Full product code	911401547861
Order product name	ST700T LED40 930PC PSU MB 1C BK
Order code	911401547861
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
Material no. (12 NC)	911401547861
SAP net weight (piece)	0.599 kg



## Dimensional drawing



ST700T Truefashion Projector GCGM

