



UniStrip G4

BCP382 9LED 27K 24V 17 L30 DMX

UniStrip G4 is a surface-mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.;One family that fits all your needs, wall washing, grazing and also linear flood lighting.;The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.;Available in white, monochromatic colours, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

General Information		Operating and Electrical	
Lamp colour code	Warm white	Input Voltage	24 DC V
Light source replaceable	No	Input frequency	- Hz
Driver included	No	Power factor (min.)	0.9
Optical cover/lens type	CLFT [Clear flat]	Controls and Dimming	
Luminaire light beam spread	17° x 17°	Dimmable	Yes
Control interface	Dynamix DMX	Mechanical and Housing	
Connection	2 push-in connectors 5-pole	Housing material	Aluminum extruded
Cable	2 cables 0.15 m with connectors 5-pole	Optic material	Polymethyl methacrylate
Protection class IEC	Safety class III (III)	Optical cover/lens material	Tempered glass
Flammability mark	F [For mounting on normally flammable surfaces]	Fixation material	Aluminium
CE mark	CE mark		
LED engine type	LED		
Serviceability class	Class B, the luminaire is equipped with some serviceable parts (when applicable): driver, control units, surge-protection device, front cover and mechanical parts		

UniStrip G4

Mounting device	MBA [Mounting bracket adjustable]
Optical cover/lens finish	Clear
Overall length	300 mm
Overall width	38 mm
Overall height	47 mm
Colour	Dark Grey

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	598 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	66 lm/W
Lamp colour temperature	2700 K
Colour Rendering Index	80
Initial chromaticity	4 SDCM

Initial input power	9 W
Power consumption tolerance	+/-10%

Application Conditions

Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Product Data

Full product code	911401739592
Order product name	BCP382 9LED 27K 24V 17 L30 DMX
Order code	911401739592
Numerator – quantity per pack	1
SAP numerator – packs per outer box	30
Material no. (12 NC)	911401739592
Net Weight (Piece)	0.599 kg



Dimensional drawing



BCP280/383/384/385 UNiStrip G3

