



UniStrip G4

BCP385 30LED 40K 220V A1 L52

UniStrip G4 is a surface-mounted, exterior-rated LED luminaire that is designed for façade and outdoor architectural lighting applications.;One family that fits all your needs, wall washing, grazing and also linear flood lighting.;The robust mechanical and unique optical designs make it ideal for illuminating buildings facades, bridges, overpasses and any application that requires a linear lighting solution.;Available in white, monochromatic colours, RGB, RGBW and tunable white and DMX control option available with up to 8 pixels (8IDs) to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Warnings and Safety

- For outdoor use only

Product data

| General Information | | Number of products on MCB (16 A type B) 4 | |
|-------------------------------|--|---|--|
| Lamp colour code | Neutral white | LED engine type | LED |
| Light source replaceable | No | Serviceability class | Class B, the luminaire is equipped with some serviceable parts (when applicable): driver, control units, surge-protection device, front cover and mechanical parts |
| Number of gear units | 1 unit | | |
| Driver/power unit/transformer | PSU [Power supply unit] | | |
| Driver included | Yes | | |
| Optical cover/lens type | GT [Tempered glass] | | |
| Luminaire light beam spread | 7.5° x 27° | | |
| Control interface | - | | |
| Connection | Flying leads/wires | | |
| Cable | Cable 0.3 m without plug 3-pole | | |
| Protection class IEC | Safety class I (I) | | |
| Flammability mark | F [For mounting on normally flammable surfaces] | | |
| CE mark | CE mark | | |
| Optic type outdoor | Asymmetrical | | |
| | | | |
| | | Light Technical | |
| | | Standard tilt angle post-top | - |
| | | Standard tilt angle side entry | - |
| | | | |
| | | Operating and Electrical | |
| | | Input Voltage | 220 to 240 V |
| | | Input frequency | 50 to 60 Hz |
| | | Inrush current | 60 A |
| | | Inrush time | 0.85 ms |

UniStrip G4

| | |
|---------------------|-----|
| Power factor (min.) | 0.9 |
|---------------------|-----|

Controls and Dimming

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Mechanical and Housing

| | |
|-----------------------------|------------------------------------|
| Housing material | Aluminum extruded |
| Optic material | Polymethyl methacrylate |
| Optical cover/lens material | Glass |
| Fixation material | Aluminium |
| Mounting device | MBA [Mounting bracket adjustable] |
| Optical cover/lens shape | Flat |
| Optical cover/lens finish | Clear |
| Overall length | 520 mm |
| Overall width | 88 mm |
| Overall height | 158 mm |
| Colour | Dark Grey |

Approval and Application

| | |
|------------------------------|---|
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK06 [1 J] |

Initial Performance (IEC Compliant)

| | |
|-------------------------------------|---------|
| Initial luminous flux (system flux) | 4114 lm |
|-------------------------------------|---------|

| | |
|--------------------------------|---------|
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 69 lm/W |
| Lamp colour temperature | 4000 K |
| Colour Rendering Index | 80 |
| Initial chromaticity | 4 SDCM |
| Initial input power | 60 W |
| Power consumption tolerance | +/-10% |

Application Conditions

| | |
|---------------------------|---------------|
| Ambient temperature range | -40 to +50 °C |
|---------------------------|---------------|

Product Data

| | |
|-----------------------------------|------------------------------|
| Full product code | 911401751912 |
| Order product name | BCP385 30LED 40K 220V A1 L52 |
| Order code | 911401751912 |
| SAP numerator – quantity per pack | 1 |
| Numerator – packs per outer box | 2 |
| Material no. (12 NC) | 911401751912 |
| SAP net weight (piece) | 2.099 kg |



Dimensional drawing



BCP280/383/384/385 UNiStrip G3

