



ZXP399 DMX Controls and Accessories

ZXP399 main controller DMX

90 to 264 V - 50 to 60 Hz - Finger-protected - CE mark - Black

The ZXP399 DMX Controls and Wiring Accessories are to be used with our architectural and facade lighting luminaires (UniFlood C, M and G, UniStrip G4, UniEdge, UniDot G2, UniString and UniBar).;DMX Controls include a main controller, stand-alone controller, sub-controllers, DMX amplifier and DMX addressing device.;Main Controller: Industrial computer that can control up to 6,000 DMX universes.;Stand-alone Controller: Fits all medium applications with up to 700 DMX universes.;Wiring accessories include leader and jump cables with male and female IP67 connectors and end-caps.;Addressing Device: Hand-held device that can write DMX addresses to a whole run on-site within minutes.;DMX Amplifier: Compact, IP65 and low-power repeater that can amplify the DMX signal for up to 100 metres.

Product data

General Information		Approval and Application	
CE mark	CE mark	Overall width	361 mm
Colour	Black	Overall height	177 mm
		Dimensions (height x width x depth)	177 x 361 x 482 mm (7 x 14.2 x 19 in)
Operating and Electrical		Product Data	
Input Voltage	90 to 264 V	Full product code	911401756612
Input frequency	50 to 60 Hz	Order product name	ZXP399 main controller DMX
Mechanical and Housing			
Overall length	482 mm		


ZXP399 DMX Controls and Accessories

Order code	911401756612
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	911401756612

SAP net weight (piece)	11.649 kg
------------------------	-----------



Dimensional drawing



ZXP399

