



PAR38

PAR38 120W E27/51 220-240V PAR38 12D 1CT

Pressed-glass 121 mm diameter reflector lamps of high luminous intensity

Product data

General Information	
Cap base	E27/51 [E27/51]
Burning Position	UNIVERSAL [Any/Universal]
Nominal lifetime (nom.)	2000 h

Light Technical	
Beam Angle (Nom)	12 °
Lamp Luminous Flux 25°C EL (Nom)	1150 lm
Luminous intensity (max.)	8200 cd
Beam description	Spot
Rated beam angle	12 °
Colour Rendering Index,horiz (Nom)	100

Operating and Electrical	
Power (Rated) (Nom)	120 W
Starting time (nom.)	0.0 s
Voltage (Nom)	220-240 V

Mechanical and Housing	
Eccentricity (max.)	1.0 mm


Skewness (max.)	2.5 mm
-----------------	--------

Luminaire Design Requirements	
Cap-base temperature (max.)	150 °C

Product Data	
Full product code	871016317088601
Order product name	PAR38 120W E27/51 220-240V PAR38 12D 1CT
EAN/UPC – product	8710163170886
Order code	923815343301
SAP numerator – quantity per pack	1
Numerator – packs per outer box	12
SAP material	923815343301
SAP net weight (piece)	308.000 g
ILCOS code	IPAR-120-220/240-E27/51-121/12

PAR38


Dimensional drawing



Product	D	C (max)	C1
PAR38 120W E27/51 220-240V PAR38 12D 1CT	121 mm	137 mm	123 mm

PAR38 120W E27/51 220-240V PAR38 SP 12D

Photometric data



LDLD_IPAR38-E_120W_SP-Light distribution diagram

